

SURVEILLANCE CAMERA SYSTEM

AND

PHOTOGRAPHING LENS SYSTEM THEREOF

5 BACKGROUND OF THE INVENTION

1. Field of the Invention

The present invention relates to a surveillance camera system and a photographing lens system thereof, and in particular, relates to a surveillance camera system (day-and-night surveillance camera system) and a photographing lens system thereof which can be used in a visible light wavelength range (400~700 nm) and a near-infrared light wavelength range (700~1000 nm).

2. Description of the Prior Art

15 In the above-mentioned type of day-and-night surveillance camera system, color photography in the day time is performed by utilizing light in the visible light wavelength range to form an image onto a color imaging device (CCD) provided in a camera body; on the other hand, 20 at night, monochrome photography is performed by utilizing light in the near-infrared light wavelength range in addition to light in the visible light wavelength range to form an image onto the color imaging device. The images formed on the color imaging device are displayed on a TV 25 monitor. In this type of surveillance camera system, a

mechanism for positioning a near-infrared light cut filter in front of the imaging device (in the camera body or in a lens barrel) in day-time photography, and for removing the near-infrared light cut filter therefrom in night
5 photography is necessary.

With respect to the correcting of aberrations in a prior art photographing lens system, since the visible light wavelength range is considered to be more important, in design, than other wavelength ranges, a large defocus
10 (a shift of an in-focus position) occurs in the near-infrared light wavelength range. Accordingly, in night photography, the near-infrared light cut filter is removed, and at the same time, for the purpose of aligning the in-focus position with the imaging surface of the imaging
15 device, a transparent plane-parallel plate for adjusting the optical path length has to be inserted. The transparent plane-parallel plate is generally formed to have a predetermined thickness different from that of the near-infrared light cut filter. In addition to the function
20 to cut near-infrared light,
the transparent plane-parallel plate can also be provided with functions to cut near-infrared light, plane-parallel plates with filtering functions to cut visible light and ultraviolet light, and to control optical density and color
25 temperatures and the like can also be provided.

In particular, in an interchangeable-lens type surveillance camera system having a photographing lens system and a camera body to which the photographing lens system is detachably attached, the amount of aberrations
5 differs depending on an interchangeable photographing lens system. It is therefore necessary to prepare a plurality of near-infrared light cut filters of different thickness, and a plurality of transparent plane-parallel plates of different thickness, in accordance with the amount of
10 aberrations in each interchangeable photographing lens system. Furthermore, a selected near-infrared light cut filter with a predetermined thickness and a selected transparent plane-parallel plate with a predetermined thickness have to be inserted in accordance with the type
15 of a photographing lens system. As a result, a photographing lens system for a day-and-night surveillance camera system of the prior art requires a selecting-and-inserting/removing mechanism for the filters and the like having different thickness. However, such a
20 mechanism inevitably makes the structure and control of the surveillance camera system complicated. In addition to the above, in a photographing lens system of the day-and-night surveillance camera system, there is a limitation that the camera system cannot be constituted
25 unless the combination of a specific camera body and a

specific photographing lens system is selected.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a
5 surveillance camera system and a photographing lens system
thereof, by which suitable photography can be performed
in both the visible light wavelength range and the
near-infrared light wavelength range.

Another object of the present invention is to provide
10 a surveillance camera system and photographing lens system
thereof, which do not require a complicated selecting-
and- inserting/removing mechanism for the filters and the
like.

The present invention is applied to a surveillance
15 camera system including a photographing lens system and
a camera body having a color imaging device on which an
image by the photographing lens system is formed; and the
photographing lens system is detachably attached on the
camera body. According to the present invention, the
20 photographing lens system itself is improved to have
suitable optical performance for a day-and-night
surveillance camera system, so that the number of the
plane-parallel plates to be inserted in front of the color
imaging device in the camera body can be reduced to two.

25 As an aspect of the present invention, the correcting

of aberrations is carried out in a photographing lens system so that the difference between (i) the in-focus position at which the maximum MTF characteristic in the visible light wavelength range of about 400nm to 700nm is
5 obtained and (ii) the in-focus position at which the maximum MTF characteristic in the near-infrared light wavelength range of about 700nm to 1000nm is obtained is less than $10\mu\text{m}$.

As another aspect of the present invention, a single
10 near-infrared light cut filter and a single transparent plane-parallel plate are alternatively inserted in front of the color imaging device in the camera body or the photographing lens system. According to this arrangement, in day time photography, the near-infrared light cut filter
15 is positioned in front of the color imaging device; on the other hand, in night photography, the transparent plane-parallel plate is positioned in front of the color imaging device. It is preferable that the product which multiplies the refractive index of the near-infrared light
20 cut filter by the thickness thereof, i.e., the optical thickness, be the same as that of the transparent plane-parallel plate.

The present invention can particularly be applied to a camera system to which a plurality of interchangeable
25 photographing lens systems are provided. For each of the

interchangeable photographing lens systems, if aberrations are corrected so that the difference between (i) the in-focus position at which the maximum MTF characteristic in the visible light wavelength range of about 400nm to 700nm is obtained and (ii) the in-focus position at which the maximum MTF characteristic in the near-infrared light wavelength range of about 700nm to 1000nm is obtained is less than 10 μ m, no optical adjustment is required even when another photographing lens system is attached to the camera body.

The present disclosure relates to subject matter contained in Japanese Patent Application No.2001-048045 (filed on February 23, 2001) which is expressly incorporated herein in its entirety.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be discussed below in detail with reference to the accompanying drawings, in which:

Figure 1 shows a schematic view of an embodiment of a surveillance camera system according to the present invention;

Figure 2 shows a schematic view of another embodiment of a surveillance camera system according to the present invention;

Figure 3 shows curves of spectral distribution of a light-source;

Figure 4 shows a curve of spectral sensitivity of a light-receiving element;

5 Figure 5 shows a curve of spectral transmittance curve of a near-infrared light cut filter;

10 Figure 6 shows a curve of the correcting of chromatic aberration, at the short focal length extremity, in a zoom photographing lens system according to the present invention;

Figure 7 shows a curve of the correcting of chromatic aberration, at the long focal length extremity, in the zoom photographing lens system according to the present invention;

15 Figures 8A and 8B show MTF (modulation transfer function) curves, at the short focal length extremity, of the zoom photographing lens system of the present invention, in the visible light wavelength range and near-infrared light wavelength range, respectively;

20 Figures 9A and 9B show MTF curves, at the long focal length extremity, of the zoom photographing lens system of the present invention, in the visible light range and near-infrared light range, respectively;

25 Figure 10 shows a curve of the correcting of chromatic aberration, at the short focal length extremity, in a zoom

photographing lens system of a prior art;

Figure 11 shows a curve of the correcting of chromatic aberration, at the long focal length extremity, in the zoom photographing lens system of a prior art;

5 Figures 12A and 12B show MTF curves, at the short focal length extremity, of the zoom photographing lens system of a prior art, in the visible light wavelength range and near-infrared light wavelength range, respectively; and

10 Figures 13A and 13B show MTF curves, at the long focal length extremity, of the zoom photographing lens system of a prior art, in the visible light wavelength range and near-infrared light wavelength range, respectively.

15 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Figures 1 and 2 show the embodiments on a surveillance camera system. The surveillance camera system includes a zoom photographing lens system 10, and a camera body 20 to which the zoom photographing lens system 10 is detachably attached. In a predetermined stationary position in the camera body 20, a color imaging device (CCD) 21 on which an object image by the zoom photographing lens system 10 is formed is provided, and a low-pass filter 22 is positioned in front of the color imaging device 21.

25 In the zoom photographing lens system 10 (figure 1)

or in the camera body 20 (figure 2), a near-infrared light cut filter 31 and a transparent plane-parallel plate 32, which are alternatively inserted in and retracted from the optical path, are provided. Since a selecting-and-
5 inserting/removing mechanism for the filters is known in the art, such a mechanism is not shown in drawings. The product which multiplies the refractive index of the near-infrared light cut filter 31 by the thickness thereof, i.e., the optical thickness, is the same as that of the
10 transparent plane-parallel plate 32.

In the zoom photographing lens system 10, the correcting of aberrations is carried out by taking the following into consideration: (i) the spectral sensitivity of the color imaging device 21; (ii) the spectral
15 transmittance of the near-infrared-cut filter 31; and (iii) the light wavelength ranges of day light and night light.

Figure 3 shows the curves of spectral distribution of a light-source. The solid-line curve indicates the
20 standard light source D65 as a light source for day light. On the other hand, the dotted-line curve indicates the standard light source A as a light source for night light. Figure 4 shows the curve of spectral sensitivity of the color imaging device 21 (a light-receiving element). The
25 spectral sensitivity is indicated as relative values so

that the maximum value thereof is normalized to 1.0. Figure 5 shows the curve of spectral transmittance of the near-infrared light cut filter 31.

Chromatic aberration is the most important factor for determining the in-focus position in day light and night light. Figures 6 and 7 show chromatic-aberration characteristics of the zoom photographing lens system 10, at the short focal length extremity and the long focal length extremity. Furthermore, numerical data of the zoom photographing lens system 10 is indicated in Table 1. For the purpose of comparison, figures 10 and 11 show chromatic-aberration characteristics of a prior art zoom photographing lens system, at the short focal length extremity and the long focal length extremity. Numerical data of the prior art zoom photographing lens system is indicated in Table 2. Note that the zoom photographing lens systems based on Tables 1 and 2 are both two-lens-group zoom photographing lens systems. Surface Nos. 18 and 19 designates the low-pass filter 22, F_{No} designates the F-number, f designates the focal length of the entire lens system, W designates the half angle-of-view ($^{\circ}$), f_B designates the back focal distance (the distance between surface No. 19 and the image surface of the color imaging device 21), r designates the radius of curvature, d designates the lens-element thickness or distance between

lens elements, N_d designates the refractive index of the d-line, and v designates the Abbe number.

[Table 1]

$F_{NO} = 1:1.4-1.9$

5 $f = 2.88-5.82$

$W = 68.9-33.2$

$f_B = 5.22-9.76$

	Surf.No.	r	d	N_d	v
10	1	26.608	1.000	1.77250	49.6
	2	8.327	3.300	-	-
	3	25.647	1.000	1.77250	49.6
	4	10.447	2.050	-	-
	5	102.077	1.000	1.72916	54.7
15	6	8.710	0.890	-	-
	7	10.014	2.670	1.84666	23.8
	8	29.920	19.68-5.52	-	-
	9	50.000	1.800	1.83481	42.7
	10	-26.470	0.120	-	-
20	11	12.800	2.530	1.62041	60.3
	12	-27.500	0.430	-	-
	13	-15.780	5.610	1.69895	30.1
	14	6.350	3.850	1.49700	81.6
	15	-12.450	0.100	-	-
25	16	37.468	1.500	1.74400	44.8
	17	-37.468	0.000	-	-

18	∞	3.500	1.49782	66.8
19	∞	-	-	-

[Table 2]

$F_{No} = 1:1.4-1.8$

5 $f = 2.86-5.85$

$W = 69.3-32.9$

$f_B = 5.21-9.78$

	Surf.No.	r	d	N_d	v
10	1	26.608	1.000	1.77250	49.6
	2	8.327	3.300	-	-
	3	25.647	1.000	1.77250	49.6
	4	10.447	2.050	-	-
	5	102.077	1.000	1.72916	54.7
15	6	8.710	0.890	-	-
	7	10.014	2.670	1.84666	23.8
	8	29.920	19.81-5.54	-	-
	9	53.304	2.000	1.83400	37.2
	10	-22.703	0.100	-	-
20	11	13.250	2.430	1.77250	49.6
	12	-70.608	0.460	-	-
	13	-19.850	5.360	1.80518	25.4
	14	6.892	3.440	1.48749	70.2
	15	-13.800	0.100	-	-
25	16	154.400	1.860	1.89400	37.2
	17	-18.700	0.000	-	-

18	∞	3.500	1.49782	66.8
19	∞	-	-	-

In the prior-art zoom photographing lens system based
 on Table 2, at the short focal length extremity, as shown
 5 in figure 10, the correcting of aberrations is carried out
 so that in the visible light wavelength range, chromatic
 aberration becomes smaller in the range from 436nm to 656nm.
 On the contrary, in the near-infrared light wavelength
 range (700nm-1000nm), chromatic aberration largely
 10 increases. Furthermore, as can be understood by comparing
 the curve shown in figure 11 with that of figure 10,
 chromatic aberration becomes larger as the focal length
 increases. On the other hand, in the zoom photographing
 lens system 10 according to the embodiment of the present
 15 invention based on Table 1, as shown in figure 6, the
 correcting of aberration is carried out so that an increase
 of chromatic aberration in the near-infrared light
 wavelength range of 700nm to 1000nm becomes smaller with
 respect to chromatic aberration in the visible light
 20 wavelength range of 400nm to 700nm. Still further, as can
 be understood by comparing the curve shown in figure 7 with
 that of figure 6, chromatic aberration at the long focal
 length extremity is substantially the same as chromatic
 aberration at the short focal length extremity, even when
 25 the focal length increases.

An actual in-focus position is influenced not only by chromatic aberration, but also by other aberrations, e.g., spherical aberration. In addition, the actual in-focus position is influenced by the spectral sensitivity of the color imaging device 21, the spectral transmittance of the near-infrared light cut filter 31, and the light wavelength ranges of day light and night light. Therefore in order to obtain an in-focus position, the above-mentioned factors, such as the spectral sensitivity of the color imaging device 21 and the like, are weighed, and influence of each wavelength to an in-focus position is considered, thereby the MTF (modulation transfer function) curves are obtained. In other words, an axial MTF value is a specific value which is obtained based on aberrations, and all the characteristics shown in figures 3 to 5, i.e., (i) the curves of spectral distribution of the light-source (figure 3); (ii) the curve of the spectral sensitivity of the color imaging device 21 (figure 4); (iii) the curve of the spectral transmittance of the near-infrared light cut filter 31 (figure 5); (iv) aberrations, specifically spherical aberration, occurred in lens elements of the zoom photographing lens system 10; and (v) chromatic aberration explained.

The in-focus position in the visible light wavelength range or the near-infrared light wavelength range can be

defined as the maximum value of each MTF value.

Figures 8A and 8B (MTF curves) show the defocus at the short focal length extremity, in the visible light wavelength range (figure 8A) and in the near-infrared light wavelength range (figure 8B), which is calculated by considering the characteristics obtained from figures 3 to 5 with respect to the zoom photographing lens system based on Table 1.

Similarly, figures 9A and 9B (MTF curves) show the defocus at the long focal length extremity, in the visible light wavelength range (figure 9A) and in the near-infrared light wavelength range (figure 9B), which is calculated by considering the characteristics obtained from figures 3 to 5 with respect to the zoom photographing lens system based on Table 1.

On the other hand, figures 12A and 12B (MTF curves) show the defocus at the short focal length extremity, in the visible light wavelength range (figure 12A) and in the near-infrared light wavelength range (figure 12B), with respect to the zoom photographing lens system based on Table 2.

Similarly, figures 13A and 13B (MTF curves) show the defocus at the long focal length extremity, in the visible light wavelength range (figure 13A) and in the near-infrared light wavelength range (figure 13B), with respect

to the zoom photographing lens system based on Table 2.

In the above figures, sampling is carried out for wavelengths in both the visible light wavelength range and the near-infrared light wavelength range, and factors
5 influencing the in-focus position are weighed according to the order of the magnitude of influence.

In figures 8A, 8A, 9A, 9B, 12A, 12B, 13A and 13B, the in-focus position is the highest peak along the MTF curve. In comparison with figures 12A through 13B of the prior
10 art, the embodiments of figures 8A through 9B can reduce the difference between the highest peak in the visible light wavelength range and the highest peak in the near-infrared light wavelength range to less than $10\mu\text{m}$. The allowance of $10\mu\text{m}$ changes in accordance with the
15 F-number, and the size of the light receiving element per pixel. For example, in a generally used photographing lens system having an F-number of 1.4, if the allowance is reduced to less than $10\mu\text{m}$, the decrease of the MTF value can be considered to be within an acceptable level. This
20 can be understood from the above-mentioned figures. Namely, in these figures, the abscissa is calibrated every $20\mu\text{m}$ (0.02 mm). If defocus is less than about half of $20\mu\text{m}$, the peak of the MTF curve is not lowered much.

In the embodiments of the zoom photographing lens
25 system 10 shown in figures 1 and 2, in daytime photography,

the near-infrared light cut filter 31 is inserted into the optical path; on the other hand, in night photography, the transparent plane-parallel plate 32 is inserted into the optical path. Since the product which multiplies the refractive index of the near-infrared light cut filter 31 by the thickness thereof, i.e., the optical thickness, is the same as that of the transparent plane-parallel plate 32, the optical path length does not change even when either the near-infrared light cut filter 31 or the transparent plane-parallel plate 32 is inserted therein,

The above description is directed to the zoom photographing lens system 10; however, the present invention can be applied to a photographing lens system for a fixed-focus camera.

The embodiments are based on only one numerical data of Table 1; however, it is easy for those who are skilled in the art to design a photographing lens system having aberration characteristics (MTF characteristics), such as figures 6 through 9B. In other words, a feature of the present invention does not reside in the design of a photographing lens system itself, but rather resides in utilizing a photographing lens system having aberration characteristics (MTF characteristics), such as figures 6 through 9B, in a day-and-night surveillance camera system.

According to the above description, a surveillance

camera system and a photographing lens system thereof, by which suitable photography can be performed in both the visible light wavelength range and the near-infrared light wavelength range, can be obtained.

- 5 Furthermore, a surveillance camera system and photographing lens system thereof, which do not require a complicated selecting-and-inserting/removing mechanism for the filters and the like, can be obtained.